



Ice Scales





Muster Series



| Muster 250 | |
|---|--|
|  | Produzione 24h* 250 kg - 551 lbs Production 24h |
| | Condensazione A - W Cooling system |
| | Consumo elettrico** 1700 W Electrical consumption |
| | Dimensioni (LxPxH) 870 x 550 x 600 mm Sizes (WxDxH) 34 4/16 x 21 10/16 x 23 10/16 " |
| | Peso netto 100 kg - 220 lbs Net weight |
| | Fusibile 16 A Fuse |
| Bin utilizzabile Bin 200 - Bin 350 Usable bin | |

| Muster 350 | |
|---|---|
|  | Produzione 24h* 400 kg - 882 lbs Production 24h |
| | Condensazione A - W Cooling system |
| | Consumo elettrico** 2100 W Electrical consumption |
| | Dimensioni (LxPxH) 900 x 588 x 705 mm Sizes (WxDxH) 35 7/16 x 23 2/16 x 27 12/16 " |
| | Peso netto 137 kg - 302 lbs Net weight |
| | Fusibile 16 A Fuse |
| Bin utilizzabile Bin 350 - Bin 550V DS Usable bin DRB 100 | |

| Muster 600 | |
|--|---|
|  | Produzione 24h* 620 kg - 1367 lbs Production 24h |
| | Condensazione A - W Cooling system |
| | Consumo elettrico** 3000 W Electrical consumption |
| | Dimensioni (LxPxH) 900 x 588 x 705 mm Sizes (WxDxH) 35 7/16 x 23 2/16 x 27 12/16 " |
| | Peso netto 151 kg - 333 lbs Net weight |
| | Fusibile 16 A Fuse |
| Bin utilizzabile Bin 350 - Bin 550V DS Usable bin DRB 100 / 500 / 1200 | |

| Muster 800 | |
|---|--|
|  | Produzione 24h* 900 kg - 1984 lbs Production 24h |
| | Condensazione A - W Cooling system |
| | Consumo elettrico** 4600 W Electrical consumption |
| | Dimensioni (LxPxH) 1107 x 700 x 880 mm Sizes (WxDxH) 43 9/16 x 27 9/16 x 34 10/16 " |
| | Peso netto 241 kg - 531 lbs Net weight |
| | Fusibile 16 A Fuse |
| Bin utilizzabile Bin 550V DS Usable bin DRB 500 / 1200 | |

| Muster 1500 | |
|--|---|
|  | Produzione 24h* 1500 kg - 3307 lbs Production 24h |
| | Condensazione A - W Cooling system |
| | Consumo elettrico**** 6000 W Electrical consumption |
| | Dimensioni (LxPxH) 1107 x 700 x 970 mm Sizes (WxDxH) 43 9/16 x 27 9/16 x 38 3/16 " |
| | Peso netto 306 kg - 675 lbs Net weight |
| | Fusibile 32 A Fuse |
| Bin utilizzabile Bin 550V DS Usable bin DRB 500 / 1200 | |

* Temp. ambiente / Ambient temp. +21° C - Temp. acqua / Water temp. +15° C

** Temp. ambiente / Ambient temp. +43° C


**** Temp. ambiente / Ambient temp. +21° C

Muster 2000




Produzione 24h* 2300 kg - 5071 lbs
Production 24h
Condensazione A
Cooling system
Consumo elettrico**** 7000 W
Electrical consumption
Dimensioni (LxPxH) 1062 x 832 x 1423 mm
Sizes (WxDxH) 41 13/16 x 32 12/16 x 56 "
Peso netto 520 kg - 1146 lbs
Net weight
Fusibile 32 A
Fuse
Bin utilizzabile -
Usable bin

Muster 350 Split




Produzione 24h* 400 kg - 882 lbs
Production 24h
Potenza frigorifera 2200 W (evap. temp. -23°C)
Cooling capacity
Consumo elettrico** 180 W
Electrical consumption
Dimensioni (LxPxH) 495 x 588 x 705 mm
Sizes (WxDxH) 19 8/16 x 23 2/16 x 27 12/16 "
Peso netto - Net weight 66 kg - 146 lbs
Bin utilizzabile Bin 350 - Bin 550V DS - DRB 100
Usable bin

Muster 600 Split



Produzione 24h* 620 kg - 1367 lbs | 620 kg - 1367 lbs
Production 24h
Potenza frigorifera 3500 W (evap. temp. -22°C)
Cooling capacity 3500 W (evap. temp. -23°C)
Consumo elettrico** 180 W
Electrical consumption
Dimensioni (LxPxH) 495x 588 x 705 mm
Sizes (WxDxH) 19 8/16 x 23 2/16 x 27 12/16 "
Peso netto - Net weight 73 kg - 161 lbs
Bin utilizzabile Bin 350 - Bin 550V DS - DRB 100 / 500 / 1200
Usable bin

Muster 800 Split



Produzione 24h* 900 kg - 1984 lbs | 1040 kg - 2293 lbs
Production 24h
Potenza frigorifera 5000 W (evap. temp. -23°C)
Cooling capacity 5000 W (evap. temp. -23°C)
Consumo elettrico** 180 W
Electrical consumption
Dimensioni (LxPxH) 604 x 700 x 880 mm
Sizes (WxDxH) 23 12/16 x 27 9/16 x 34 10/16 "
Peso netto - Net weight 138 kg - 304 lbs
Bin utilizzabile Bin 550V DS - DRB 500 / 1200
Usable bin

* Temp. ambiente / Ambient temp. +21° C - Temp. acqua / Water temp. +15° C

** Temp. ambiente / Ambient temp. +43° C

**** Temp. ambiente / Ambient temp. +21° C